

15350 - Eco multi dos. anlæg til 4 midler, high flow

Standard hvid doseringshjul - til opfyldning af spande og gulvvaskere. Se dyseoversigt for dosering af kemi fra Stadsing



High Flow Standard Dilution				
Flow rate: 13 Ltrs/min 4 US Gal/min				
	Dilution Ratio	%	oz/gal	ml/ltr
A	12:1	7.7%	9.8	77
B	19:1	5.0%	6.4	50
C	30:1	3.2%	4.1	32
D	40:1	2.4%	3.1	24
E	50:1	2.0%	2.5	20
F	60:1	1.6%	2.1	16
G	75:1	1.3%	1.7	13
H	100:1	1.0%	1.3	10
I	128:1	0.8%	1.0	8
J	160:1	0.6%	0.8	6
K	256:1	0.4%	0.5	4
L	350:1	0.3%	0.4	3

15431 - IQ doseringsanlæg low flow t/koncentratprodukter

Ultra rød doseringshjul - til opfyldning af sprayflasker. IQ produkter fra Stadsing: 17418, 17419, 17420 og 17421 sættes til dosering L



Low Flow Ultra Dilution				
Flow rate: 4.5 Ltrs/min 1 US Gal/min				
	Dilution Ratio	%	oz/gal	ml/ltr
A	6:1	14.3%	18.3	143
B	9:1	10.0%	12.8	100
C	12:1	7.7%	9.8	77
D	15:1	6.3%	8.0	63
E	20:1	4.8%	6.1	48
F	25:1	3.8%	4.9	38
G	30:1	3.2%	4.1	32
H	40:1	2.4%	3.0	24
I	80:1	1.2%	1.5	12
J	120:1	0.8%	1.1	8
K	170:1	0.6%	0.7	6
L	230:1	0.4%	0.5	4