



TECHNICAL SHEET FA 40 906 50

WORK POSITIONING LANYARD WITH ROPE GRAB ADJUSTER, MAX. 5 M



- Made up of 12mm diam. polyamide Kernmantle rope.
- Aluminium rope grab adjuster, for a progressive movement.
- Mobile protective sleeve against abrasion and cuts, length 1.60 m.
- Abrasion resistant thimble to protect the loops from being damaged by contact with metal parts.
- Sewings protected under a strong protective sleeve which allow a visual checking of the sewings.

Connectors :

1 steel screw-locking karabiner FA 50 101 17, opening 18 mm et 1 steel snap hook FA 50 202 17, opening 16 mm.

Compliance : EN358 : 2000

Material of components:

Lanyard: Polyamide kernmantle rope

Grip adjuster : Aluminium

Connectors : Steel

Length :	CE	Weight :
5 m maxi		0.75 kg

KRATOS SAFETY

689 Chemin du Buclay
38540 Heyrieux – FRANCE

Tel. : +33 (0)4 72 48 78 27

Fax : +33 (0)4 72 48 58 32

www.kratossafety.com / info@kratossafety.com

HS CODE

7616 10 00

SIZE CARTON / PIECES

60 x 40 x 24 cm / 10

AET N° 4016 I3 E3

Satra Technology Centre, N°0321
Wyndham Way, Telford Way, Kettering
Northamptonshire, NN16 8SD, United Kingdom

ARTICLE 11 GB07/73551

SGS United Kingdom Ltd., N°0120
Unit 202B, Worle Parkway,
Weston-super-Mare, BS22 6WA, United Kingdom